

FG-Line Polycarbonate cover

Anti-corrosive luminaires for T8 lamps

- Corrosion-resistant light grey G.R.P. moulded body
- High-impact resistant prismatic polycarbonate cover
- Covers secured with durable stainless steel clips
- Quick-release turnbuckles make gear tray removal simple. Hangs on safety straps for easy maintenance
- Through wiring facility option
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas



IP65  

Range

NOMINAL SIZE (mm)	LAMP	CAT. No.	LENGTH (mm)	FIXINGS	APPROX. kg	STANDARD CIRCUIT	EMERGENCY CIRCUIT	AUTOTEST CIRCUIT
600	2 x 18W T8	PFG 13002	666	Drill 2 holes on 230mm centres	3.7	J	J	J
1200	1 x 36W T8	PFG 13003	1276	Drill 2 holes on 836mm centres	3.2	E-J-S	E-J	E-J
	2 x 36W T8	PFG 13004			4.6	E-J-S	J	J
1500	1 x 58W T8	PFG 13005	1576	Drill 2 holes on 1136mm centres	4.2	E-J-S	E-J	E-J
	2 x 58W T8	PFG 13006			6.9	E-J-S	J	-
1800	1 x 70W T8	PFG 6367▲	1850	2 x 6.5mm dia. knock-outs on 1390mm centres	4.9	E-J-S	E-J	E-J
	2 x 70W T8	PFG 6366▲			8.0	E-J-S	J●	-

FACTORY FITTED THROUGH WIRING WITH METAL GLAND EARTHING LUGS - add 'TW' after catalogue number eg. **PFG 13003JTW**

CIRCUIT - add suffix required:

E - electronic start J - high frequency S - switch start e.g. **PFG 13003J** etc.

EMERGENCY VERSION - prefix catalogue number with 'EFP'.

AUTOTEST VERSION - prefix catalogue number with 'TFP'.

Emergency and AutoTest versions add 0.7kg to weights listed.

● Fitting plus 230 x 80 x 86mm remote polycarbonate battery box (Classified: IP65).

▲ 1800mm versions have a deeper cover with external prisms.

LOW TEMPERATURE VERSIONS (down to -40°C) - Contact our Technical Department for further details.

LAMPS MUST BE ORDERED SEPARATELY




Installation Kits One kit is required per luminaire installed

KIT	CAT. No.	DESCRIPTION	APPROX. kg
Hook suspension	IK 6388	Two stainless steel hooks with sealing washers for chain suspension	0.05
IP65 gland kit	IK 6389	Weatherproof nylon gland with sealing washers for 20mm entry of flexible cables	0.02
Conduit entry	IK 6390	IP65 20mm conduit suspension sealing washer kit	0.01
Rod suspension	IK 6391	IP65 10mm diameter rod sealing washer kit	0.01

Photometric Guide


1 LAMP

D.L.O.R. 53% U.L.O.R. 13%




2 LAMP


D.L.O.R. 52% U.L.O.R. 9%



600/1200/1500mm VERSIONS



1800mm VERSIONS



FG-Line Acrylic cover

Anti-corrosive luminaires for T8 lamps

- Corrosion-resistant light grey G.R.P. moulded body
- Covers secured with durable stainless steel clips
- Quick-release turnbuckles make gear tray removal simple. Hangs on safety straps for easy maintenance
- Through wiring facility option

IP65  



Range

NOMINAL SIZE (mm)	LAMP	CAT. No.	LENGTH (mm)	FIXINGS	APPROX. kg	STANDARD CIRCUIT	EMERGENCY CIRCUIT	AUTOTEST CIRCUIT
600	2 x 18W T8	AFG 13010	666	Drill 2 holes on 230mm centres	3.7	J	J	J
1200	1 x 36W T8	AFG 13011	1276	Drill 2 holes on 836mm centres	3.2	J	J	J
	2 x 36W T8	AFG 13012			4.6	J	J	J
1500	1 x 58W T8	AFG 13013	1576	Drill 2 holes on 1136mm centres	4.2	E-J-S	E-J	E-J
	2 x 58W T8	AFG 13014			6.9	E-J-S	J	-
1800	1 x 70W T8	VFG 6359▲▲	1850	2 x 6.5mm dia. knock-outs on 1390mm centres	4.5	E-J-S	E-J	E-J
	2 x 70W T8	VFG 6358▲▲			7.5	E-J-S	J●	-

FACTORY FITTED THROUGH WIRING WITH METAL GLAND EARTHING LUGS - add 'TW' after catalogue number eg. [AFG 13010JTW](#)

CIRCUIT - add suffix required:

E - electronic start J - high frequency S - switch start e.g. [AFG 13010J](#) etc.

EMERGENCY VERSION - prefix catalogue number with 'EFA' (+ 1800mm versions prefix catalogue number with 'EFV').

AUTOTEST VERSION - prefix catalogue number with 'TFA' (+ 1800mm versions prefix catalogue number with 'TFV').

Emergency and AutoTest versions add 0.7kg to weights listed.

● Fitting plus 230 x 80 x 86mm remote polycarbonate battery box (Classified: IP65).

▲ 1800mm versions have a deeper cover.

LOW TEMPERATURE VERSIONS (down to -40°C) - Contact our Technical Department for further details.

LAMPS MUST BE ORDERED SEPARATELY




Installation Kits One kit is required per luminaire installed

KIT	CAT. No.	DESCRIPTION	APPROX. kg
Hook suspension	IK 6388	Two stainless steel hooks with sealing washers for chain suspension	0.05
IP65 gland kit	IK 6389	Weatherproof nylon gland with sealing washers for 20mm entry of flexible cables	0.02
Conduit entry	IK 6390	IP65 20mm conduit suspension sealing washer kit	0.01
Rod suspension	IK 6391	IP65 10mm diameter rod sealing washer kit	0.01

Photometric Guide


1 LAMP

D.L.O.R. 62% U.L.O.R. 12%




2 LAMP

D.L.O.R. 62% U.L.O.R. 8%



600/1200/1500mm VERSIONS
Injection moulded prismatic acrylic cover



1800mm VERSIONS
Vacuum formed stippled acrylic cover

