



Delta 72

Typical applications include:

- Ice rinks
- Sports facilities
- Health & exercise
- Gymnasiums
- Refrigeration & cold stores
- Processing area lighting
- Warehousing



constellation
LIGHTING UK & EUROPE



Constellation Lighting Ltd Unit 1, Holbrook Industrial Estate, Halfway, Sheffield S20 3FG
T + 44 (0)114 2479900 F + 44 (0)1142478351 www.constellationlighting.eu



technical specifications

Delta 72 150W

| | |
|-------------------------|---------------------------|
| Input Voltage | 100 - 277v AC 50 / 60 Hz |
| Operating Temperature | -20° C to 50 ° C |
| Ingress Protection | IP65 |
| Colour Temperature | 5800K |
| Colour Rendering Index | >80 |
| Lifespan | Typically 80,000 hrs* |
| Total Power Consumption | 150W (13,300lm) |
| Number of LED's | 72 |
| Power Factor | >0.9 |
| Harmonics | EN61000-3-2 and 61000-3-3 |
| Safety Standard | EN60598 |
| EMC/ EMI Standard | EN 61547 / EN55015 |

Distributed by:



011 (281) 882-8300
www.sourceiex.com

* LED life is quantified by equity depreciation which typically occurs at 50,000 + hours.

Constellation Lighting reserves the right to alter product offerings and specifications at any time without notice. This publication may include technical inaccuracies.